

## Interior dispersion paint dull matte, highly wet-scrub resistant, good opacity easy-to-clean, high quality

Basis

Dispersion based on vinyl acetate/ethylene/acrylate and styrene acrylate

	Guide Formulation of Wacker Chemie			LA006MM30AP
	Water			211
	Benaqua 4000 Agitan 281		(1)	3
			(2)	4
	Coadis 234 K		(3)	4
	AMP-90		(4)	2
	Kronos 2300 Portafill G 25 AKTISIL MAM Vinnapas EAF 380		(5)	200
			(6)	83
			(7)	83
			(8)	293
	Primis SAF 9000	(8)	89	
	Coapur XS 71, 25 % in water Silres BS 168 Texanol		(3)	10
			(8)	3
			(9)	15
	Total parts by weight			1000
Properties	PVC		%	approx. 40
	Gloss 60°	DIN EN ISO 2813	GU	4
	Gloss 85°	DIN EN ISO 2813	GU	5 (dull matte)
	Wet-scrub resistance	DIN EN ISO 11998	μm	1 (class 1)
	Hiding power at 8 m²/l	DIN ISO 6504-3	%	98.6 (class 2)
	Household stains			coffee, lipstick, highlighter, pencil
Suppliers	<ul> <li>(1) Elementis</li> <li>(2) Münzing Chemie</li> <li>(3) Coatex (Arkema)</li> <li>(4) Advancion</li> </ul>			

- (5) **Kronos International**
- (6) Sibelco
- HOFFMANN MINERAL (7)
- (8) Wacker Chemie
- Eastman Chemical Company (9)

Our applications engineering advice and the information contained in this formulation are based on experience and are made to the best of our knowledge and belief, they must be regarded however as non-binding advice without guarantee. Working and employment conditions over which we have no control exclude any damage claim arising from the use of our data and recommendations. Furthermore we cannot assume any responsibility for patent infringements, which might result from the use of our information.

Münchener Straße 75

• DE-86633 Neuburg (Donau) Phone +49 8431 53-0 • info@hoffmann-mineral.com

