

GLOXIL light iM16k A **in Polyamide and Polypropylene –** **The Easy Way towards Future.**

Author: Hubert Oggermüller



Contents

- Introduction
- Experimental
- Results
- Summary



Status Quo

INTRODUCTION

EXPERIMENTAL

RESULTS

SUMMARY

- In recent years, the topic of lightweight construction has steadily increased in importance, especially in the area of traffic and transport.
- Thermoplastics play an important role here, including polyamide and polypropylene. These already have relatively low densities and thus component weights.
- Various options are available for further weight optimization, and hollow glass microspheres play a particularly important role here.
- 3M™ Glass Bubbles are used for this purpose due to their positive properties.
- Surface functionalization by means of covalent bonding of organofunctional silane is a suitable method for optimizing mechanical properties.



Objective

INTRODUCTION

EXPERIMENTAL

RESULTS

SUMMARY

To show positive effects of surface functionalization in

- Polyamide PA6 and
- Polypropylene Copolymer

of **GLOXIL light iM16k A** compared to 3M™ Glass Bubbles iM16k on the mechanical property profile



Surface Functionalization

A special process creates the **GLOXIL light iM16k A** based on the micro hollow glass sphere 3M™ Glass Bubble iM16k

INTRODUCTION



EXPERIMENTAL

RESULTS

SUMMARY



**3M™ Glass Bubbles
iM16k**



GLOXIL light iM16k A



Characteristics GLOXIL light iM16k A **HOFFMANN MINERAL®**

INTRODUCTION

EXPERIMENTAL

RESULTS

SUMMARY

Density	[g/cm ³]	0.46
Particle size D ₅₀	[μm]	22
Particle size D ₉₇	[μm]	45
Specific surface area BET	[m ² /g]	2
Air jet screening > 125 μm	[%]	0.2
Flotation rate	[%]	96
pH		10
Color L* (CIELAB)		98
Functionalization		Amino

Typical properties, no specification



Selection

HOFFMANN
MINERAL®

INTRODUCTION

EXPERIMENTAL

RESULTS

SUMMARY

Polyamide PA6
Ultrad® B3K



Hollow glass bubbles only

Combination



Glass fibers + hollow glass
bubbles

PP Copolymer
Bormod™ BF970MO



Hollow glass bubbles only

Combination



Talc / hollow glass bubbles

to Overall Summary





PA6 Compound Formulations

**HOFFMANN
MINERAL®**

Objective:

Density / weight reduction and still good mechanical properties

PA Compound Ultramid® B3K BASF Melt volume rate MVR 160 cm³/10 min (275 °C, 5 kg)		
3M™ Glass Bubbles iM16k	0 to 14 % (m/m) 0 to 29 % (v/v)	---
GLOXIL light iM16k A	---	0 to 14 % (m/m) 0 to 29 % (v/v)
Total	100	100


All results were determined in the freshly molded (dry) state

Data determined by 3M Advanced Materials Division, Special Additives Laboratory



Density and Weight Reduction

measured





Tensile Modulus


INTRODUCTION

EXPERIMENTAL

RESULTS

PA6

SUMMARY





Flexural Modulus


INTRODUCTION

EXPERIMENTAL

RESULTS

PA6

SUMMARY





Yield Stress

HOFFMANN
MINERAL®


INTRODUCTION

EXPERIMENTAL

RESULTS

PA6

SUMMARY





Yield Strain

HOFFMANN
MINERAL®


INTRODUCTION

EXPERIMENTAL

RESULTS

PA6

SUMMARY





Flexural Strength


INTRODUCTION

EXPERIMENTAL

RESULTS

PA6


SUMMARY





Flexural strain

at flexural strength





Impact Strength Charpy


INTRODUCTION

EXPERIMENTAL

RESULTS

PA6

SUMMARY





Notched Impact Strength Charpy

HOFFMANN
MINERAL®


INTRODUCTION

EXPERIMENTAL

RESULTS

PA6

SUMMARY





Summary

PA6

HOFFMANN
MINERAL®

INTRODUCTION

EXPERIMENTAL

RESULTS

PA6

SUMMARY

GLOXIL light iM16k A shows in comparison to the untreated hollow glass spheres:

- Same density and thus weight saving potential
- Comparable increase in stiffness (tensile modulus and flexural modulus)
- + Significantly higher yield stress, largely independent of the filler content at the level of the unfilled PA6
- + Significantly higher yield strain, largely independent of the filler content at the level of unfilled PA6
- + Significantly higher flexural strength, with increasing filler content even higher than the unfilled PA6
- + Slightly higher impact strength
- + Slightly higher notched impact strength
- **Objective achieved:**
density / weight reduction and good mechanical properties
- + Expectation: improved scratch resistance





More Results PA6 Glass Fibers + Glass Bubbles

**HOFFMANN
MINERAL®**

Objective:

Increase of filler content/stiffness without increase of density/weight and still good mechanical properties

INTRODUCTION

EXPERIMENTAL

PA6 GF15
+ Glass Bubbles

RESULTS

SUMMARY

PA Compound Ultramid® B3K BASF Melt volume rate MVR 160 cm³/10 min (275 °C, 5 kg)			
Glass fibers	15 % (m/m) 8 % (v/v)	17 % (m/m) 8 % (v/v)	17 % (m/m) 8 % (v/v)
3M™ Glass Bubbles iM16k	---	4 % (m/m) 10 % (v/v)	---
GLOXIL light iM16k A	---	---	4 % (m/m) 10 % (v/v)
Total	100	100	100


Data determined by 3M Advanced Materials Division, Special Additives Laboratory



Density

measured

g/cm³



INTRODUCTION

EXPERIMENTAL

RESULTS

PA6 GF15
+ Glass Bubbles

SUMMARY



Tensile Modulus

HOFFMANN
MINERAL®


INTRODUCTION

EXPERIMENTAL

RESULTS

PA6 GF15
+ Glass Bubbles

SUMMARY





Flexural Modulus

HOFFMANN
MINERAL®


INTRODUCTION

EXPERIMENTAL

RESULTS

PA6 GF15
+ Glass Bubbles

SUMMARY





Tensile Strength

HOFFMANN
MINERAL®


INTRODUCTION

EXPERIMENTAL

RESULTS

PA6 GF15
+ Glass Bubbles

SUMMARY





Tensile Strain at Break


INTRODUCTION

EXPERIMENTAL

RESULTS

PA6 GF15
+ Glass Bubbles

SUMMARY





Flexural Strength

HOFFMANN
MINERAL®


INTRODUCTION

EXPERIMENTAL

RESULTS

PA6 GF15
+ Glass Bubbles

SUMMARY





Impact Strength Charpy

HOFFMANN
MINERAL®


INTRODUCTION

EXPERIMENTAL

RESULTS

PA6 GF15
+ Glass Bubbles

SUMMARY





Notched Impact Strength Charpy

HOFFMANN
MINERAL®


INTRODUCTION

EXPERIMENTAL

RESULTS

PA6 GF15
+ Glass Bubbles

SUMMARY





Summary

PA6 GF15 + Glass Bubbles

HOFFMANN
MINERAL®

INTRODUCTION

EXPERIMENTAL

RESULTS

PA6 GF15
+ Glass Bubbles

SUMMARY

GLOXIL light iM16k A as an additive to **PA6 GF 15** shows in comparison to PA6 GF15 without hollow glass spheres:

- Slightly lower impact strength
- Slightly reduced density and thus weight saving potential
- + Increase in stiffness (tensile modulus and flexural modulus)
- + Increase in tensile strength with unchanged tensile strain at break
- + Increase in flexural strength
- + Increase in notched impact strength
- Objective achieved: higher stiffness without increase in density/weight and good mechanical properties
- + Expectation: improved scratch resistance





PP Copolymer Compound Formulations

**HOFFMANN
MINERAL®**

Objective:

Density / weight reduction and still good mechanical properties

PP Compound Copolymer Bormod™ BF970MO

Borealis

MFR 20 g/10 min (230 °C, 2.16 kg)

3M™ Glass Bubbles iM16k

0 to 25 % (m/m)

0 to 40 % (v/v)

Scona TPPP 2112 GA

PP-g-MAH, approx. 1 % MAH, Byk

5 % (m/m)

GLOXIL light iM16k A

0 to 25 % (m/m)

0 to 40 % (v/v)

Total

100


100

Data determined by 3M Advanced Materials Division, Special Additives Laboratory



Density and Weight Reduction

measured; % m/m hollow glass spheres





Tensile Modulus

HOFFMANN
MINERAL®


INTRODUCTION

EXPERIMENTAL

RESULTS

PP-Copolymer

SUMMARY





Flexural Modulus

HOFFMANN
MINERAL®


INTRODUCTION

EXPERIMENTAL

RESULTS

PP-Copolymer

SUMMARY





Tensile Strength

HOFFMANN
MINERAL®


INTRODUCTION

EXPERIMENTAL

RESULTS

PP-Copolymer

SUMMARY





Flexural Strength


INTRODUCTION

EXPERIMENTAL

RESULTS

PP-Copolymer

SUMMARY





Impact Strength Charpy


INTRODUCTION

EXPERIMENTAL

RESULTS

PP-Copolymer

SUMMARY





Notched Impact Strength Charpy

HOFFMANN
MINERAL®


INTRODUCTION

EXPERIMENTAL

RESULTS

PP-Copolymer

SUMMARY





Summary

PP Copolymer

HOFFMANN
MINERAL®

GLOXIL light iM16k A shows in comparison to the untreated hollow glass spheres:

- Same density and thus weight saving potential
- Comparable increase in stiffness (tensile and flexural modulus)
- + Significantly higher tensile strength, largely independent of the filler content at the level of the unfilled PP copolymer
- + Significantly higher flexural strength, with increasing filler content even higher than the unfilled PP copolymer
- + Higher impact strength
- + Higher notched impact strength
- **Objective achieved:**
density / weight reduction and good mechanical properties
- + Expectation: improved scratch resistance and reduced visibility of scratch marks

Note on efficient dosing of PP-g-MAH:

Concentration should be in the range of 10 to 15 % (m/m), based on the GLOXIL light iM16k A dosage (applies to MAH content in PP-g-MAH of approx. 1 %, for other contents the concentration should be adjusted accordingly)





More Results PP Talc / Glass Bubbles

**HOFFMANN
MINERAL®**

Objective:

Density / weight reduction and still good mechanical properties

INTRODUCTION

EXPERIMENTAL

PP-Copolymer

Talc / Glass Bubbles

RESULTS

SUMMARY

PP Compound Copolymer Bormod™ BF970MO					
Borealis					
MFR 20 g/10 min (230 °C, 2.16 kg)					
Talc	20 % (m/m) 7 % (v/v)	10 % (m/m) 3 % (v/v)	10 % (m/m) 3 % (v/v)	10 % (m/m) 3 % (v/v)	---
Fusabond® P 613 PP-g-MAH 0.5 to 1 % MAH, Dow	---	6 % (m/m) 6 % (v/v)	6 % (m/m) 6 % (v/v)	6 % (m/m) 6 % (v/v)	5 % (m/m) 4 % (v/v)
3M™ Glass Bubbles iM16k	---	5 % (m/m) 10 % (v/v)	---	---	---
GLOXIL light iM16k A	---	---	5 % (m/m) 10 % (v/v)	5 % (m/m) 10 % (v/v)	10 % (m/m) 18 % (v/v)
Infuse™ 9000 Olefin Block Copolymer	---	---	---	10 % (m/m) 10 % (v/v)	---
Total	100	100	100	100	100


Data determined by 3M Advanced Materials Division, Special Additives Laboratory



Density and Weight Reduction

measured

g/cm³



INTRODUCTION

EXPERIMENTAL

RESULTS

PP-Copolymer
Talc / Glass Bubbles

SUMMARY



Tensile Modulus


INTRODUCTION

EXPERIMENTAL

RESULTS

PP-Copolymer
Talc / Glass Bubbles

SUMMARY





Yield Stress


INTRODUCTION

EXPERIMENTAL

RESULTS

PP-Copolymer
Talc / Glass Bubbles

SUMMARY





Impact Strength Charpy

HOFFMANN
MINERAL®


INTRODUCTION

EXPERIMENTAL

RESULTS

PP-Copolymer
Talc / Glass Bubbles

SUMMARY





Notched Impact Strength Charpy

HOFFMANN
MINERAL®


INTRODUCTION

EXPERIMENTAL

RESULTS

PP-Copolymer
Talc / Glass Bubbles

SUMMARY





Summary PP Copolymer Talc / Glass Bubbles

HOFFMANN
MINERAL®

GLOXIL light iM16k A shows as **partial and full replacement of talc** compared to PP Copo T20 without hollow glass spheres:

- Full replacement: slightly lower stiffness
- Partial replacement: comparable stiffness
- + Reduced density / weight saving potential up to 21 %
- + Increase in yield stress (and thus potential for introduction of impact modifier)
- + Hardly any loss of yield stress despite impact modifier
- + Comparable yield stress at full replacement
- + Increase in impact strength, especially with addition of impact modifier
- + Increase in notched impact strength, especially with addition of impact modifier
- + Comparable notched impact strength at full replacement
- **Objective achieved:**
density / weight reduction and good mechanical properties
- + Expectation: improved scratch resistance





Summary Overall

INTRODUCTION

EXPERIMENTAL

RESULTS

SUMMARY

GLOXIL light iM16k A shows in comparison to the untreated hollow glass spheres:

- Same density and thus weight saving potential
- Comparable increase in stiffness (tensile and flexural modulus)
- + Significantly higher yield stress or tensile strength, largely independent of the filler content at the level of the unfilled polymer
- + Significantly higher flexural strength, with increasing filler content in some cases even higher than the unfilled polymer
- + Higher impact strength
- + Higher notched impact strength
- + Various possibilities for compound modification with e.g. impact modifiers without loss of other properties
- + Expectation: improved scratch resistance



We supply material for good ideas!

HOFFMANN MINERAL GmbH
Muenchener Straße 75
DE-86633 Neuburg (Donau)

Phone: +49 8431 53-0
Internet: www.hoffmann-mineral.de
E-mail: info@hoffmann-mineral.com

Our applications engineering advice and the information contained in this memorandum are based on experience and are made to the best of our knowledge and belief, they must be regarded however as non-binding advice without guarantee. Working and employment conditions over which we have no control exclude any damage claim arising from the use of our data and recommendations. Furthermore we cannot assume any responsibility for patent infringements, which might result from the use of our information.