

**INDUSTRIAL AND HOUSEHOLD CLEANER****Stove cleaner**

		RR 017
Exxsol D 145/160	(1)	20.0
Paraffin 54/56		2.0
Wacker AK 350	(2)	0.5
Marlipal O13/90	(3)	2.0
Emulsogen OG	(4)	2.0
Water, softened		27.3
Aluminum oxide P 10 feinst	(5)	20.0
SILLITIN P 87 PURISS	(6)	25.0
Ammonia 25 %		1.0
Preservative		(as needed) 0.2
Total % by weight		100.0

- Mixing**
- heat Exxsol D 145/160, Paraffin 54/56 and Wacker AK 350 to 65 °C to melt the wax
  - add Marlipal O13/90 and Emulsogen OG
  - heat water to approx. 70 °C and stir in
  - stir in Aluminum oxide P 10 feinst and SILLITIN P 87 PURISS with a high speed mixer
  - add ammonia
  - add preservative

- Suppliers**
- (1) ExxonMobil
  - (2) Wacker
  - (3) Sasol
  - (4) Clariant
  - (5) Almatic
  - (6) HOFFMANN MINERAL

Our applications engineering advice and the information contained in this formulation are based on experience and are made to the best of our knowledge and belief, they must be regarded however as non-binding advice without guarantee. Working and employment conditions over which we have no control exclude any damage claim arising from the use of our data and recommendations. Furthermore we cannot assume any responsibility for patent infringements, which might result from the use of our information.